

GUJARAT TECHNOLOGICAL UNIVERSITY**M. E. - SEMESTER – II • EXAMINATION – SUMMER • 2013****Subject code: 1721503****Date: 03-06-2013****Subject Name: Advanced Foundation Engineering****Time: 10.30 am – 01.00 pm****Total Marks: 70****Instructions:**

1. Attempt all questions.
2. Make suitable assumptions wherever necessary.
3. Figures to the right indicate full marks.

- Q.1** (a) What are the typical characteristics of GSF and LSF? **07**
 (b) A rectangular footing 1.8 m x 3.0 m rests on a c- ϕ soil with its base at 1.5 m below ground surface. Calculate the safe bearing capacity using a factor of safety of 3 against shear failure. Use IS method. The soil has following parameters. $C = 8 \text{ kN/m}^2$, $\phi = 32^\circ$, $\gamma = 18.0 \text{ kN/m}^3$, $N_c = 35.49$, $N_q = 23.18$, $N_{\gamma} = 30.22$. **07**
- Q.2** (a) Under what conditions Raft foundations are used? Draw typical sketch of raft foundation. **07**
 (b) Explain differential settlement. What are the causes of differential settlement? **07**
- OR**
- (b) What are the different methods to design Raft foundation? Explain any one in detail. **07**
- Q.3** (a) Draw neat sketch of well foundation and explain grip length for wells. **07**
 (b) Explain different method to rectify the tilting of well with sketches. **07**
- OR**
- Q.3** (a) Elaborate the use of finite element method for the analysis of raft foundation. **07**
 (b) How subgrade modulus is determined in field? Give its limiting values for different types of soils. **07**
- Q.4** (a) Define: Anvil, Tup, Foundation block, Protective cushion layer, Foundation support. **07**
 (b) What are the advantages and applications of reinforced earth structures? **07**
- OR**
- Q.4** (a) Describe function and properties of geotextile with sketches. **07**
 (b) Describe design criteria to design of foundation for reciprocating type machine. **07**
- Q.5** (a) Prepare short note on pile driving technique. **07**
 (b) Design a friction pile group to carry a total load of 3000 kN for uniform clay to a depth of 19 m underlain by rock. Average unconfined compressive strength of the clay is 70 kN/m^2 . A factor of safety 3 is required against shear failure. **07**
- OR**
- Q.5** (a) What is vibro-pile? Describe different stages in forming a vibro-expanded pile step by step. **07**
 (b) A reinforced concrete pile is driven into the ground by a drop hammer weighing 42 kN. Determine the ultimate bearing capacity and the allowable load for the pile. The remaining data as under: (1) Weight of pile = 32 kN, (2) Effective fall of hammer = 0.8 m, (3) Average set per blow = 1.4 cm, (4) Total temporary elastic compression = 1.8 cm, (5) Coefficient of restitution = 0.25, (6) Factor of safety = 2. **07**